

Digital Blood Pressure Monitor

Model UA-782

Instruction Manual

1WMPD4001900C

Contents

Dear Customers	
Preliminary Remarks	.2
Precautions	
Parts Identification	. 3
Symbols	.4
Operation Mode	
Using the Monitor	
Installing / Changing The Batteries	.6
Installing The Cuff Holder	.6
Connecting The Air Hose	. 7
Connecting The AC Adapter	. 7
Selecting The Correct Cuff	
Applying The Arm Cuff	. 8
How To Take Proper Measurements	. 8
Measurement	. 8
After Measurement	. 8
Measurements	.9
Normal Measurement	.9
Measurement With The Desired Systolic Pressure	0
Notes For Proper Measurement	
About Memory	
Recalling Data1	
Clearing Data	
What Is An Irregular Heartbeat1	
Pressure Bar Indicator	
WHO Classification Indicator	2
About Blood Pressure	3
What Is Blood Pressure?1	
What Is Hypertension And How Is It Controlled?	3
Why Measure Blood Pressure At Home?	3
WHO Blood Pressure Classification	
Blood Pressure Variations	
Troubleshooting	
Maintenance	
Technical Data	

Dear Customers

Congratulations on purchasing a state-of-the-art A&D blood pressure monitor, one of the most advanced monitors available today. Designed for ease of use and accuracy, this device will facilitate your daily blood pressure regimen. We recommend that you read through this manual carefully before using

Preliminary Remarks

- □ This device conforms to the European Directive 93/42 EEC for Medical Products. This is made evident by the $C \in O_{1/23}$ mark of conformity. (0123: The reference number to the involved notified body)
- The device is designed for use on adults only, not newborns or infants.
- Environment for use. The device is for use in the home healthcare environment.
- This device is designed to measure blood pressure and pulse rate of people for diagnosis.

Precautions

- Precision components are used in the construction of this device. Extremes in temperature, humidity, direct sunlight, shock or dust should be avoided.
- Clean the device and cuff with a dry, soft cloth or a cloth dampened with water and a neutral detergent. Never use alcohol, benzene, thinner or other harsh chemicals to clean the device or cuff.
- Avoid tightly folding the cuff or storing the hose tightly twisted for long periods, as such treatment may shorten the life of the components.
- The device and cuff are not water resistant. Prevent rain, sweat and water from soiling the device and cuff.
- Measurements may be distorted if the device is used close to televisions, microwave ovens, cellular telephones, X-ray or other devices with strong electrical fields.
- Used equipment, parts and batteries are not treated as ordinary household waste, and must be disposed of according to the applicable local regulations.
- When the AC adapter is used, make sure that the AC adapter can be readily removed from the electrical outlet when necessary.
- When reusing the device, confirm that the device is clean.
- Do not modify the device. It may cause accidents or damage to the device.
- To measure blood pressure, the arm must be squeezed by the cuff hard enough to temporarily stop blood flow through the artery. This may cause pain, numbness or a temporary red mark to the arm. This condition will appear especially when measurement is repeated successively. Any pain, numbness, or red marks will disappear with time.

Contraindications

The following are precautions for proper use of the device.

- Do not apply the cuff on an arm with another medical electrical equipment attached. The equipment may not function properly.
- People who have a severe circulatory deficit in the arm must consult a doctor before using the device, to avoid medical problems.
- Do not self-diagnose the measurement results and start treatment by yourself.
 Always consult your doctor for evaluation of the results and treatment.
- Do not apply the cuff on an arm with an unhealed wound.
- Do not apply the cuff on an arm receiving an intravenous drip or blood transfusion. It may cause injury or accidents.

- Do not use the dvice where flammable gases such as anesthetic gases are present. It may cause an explosion.
- Do not use the device in highly concentrated oxygen environments, such as a high-pressure oxygen chamber or an oxygen tent. It may cause a fire or explosion.



	Symbol	S
Symbols	Function / Meaning	Recommended Action
Ċ	Standby and Turn the device on.	
	Battery installation guide	
	Direct current	
Ŕ	Type BF: Device, cuff and tubing are designed to provide special protection against electrical shocks.	
•	The indicator that appears while measurement is in progress. It blinks when the pulse is detected.	Measurement is in progress. Remain as still as possible.
«(\)»	Irregular Heartbeat indicator. (I.H.B.) The indicator that appears when an irregular heartbeat or any excessive body movement is detected during the measurement.	
м	Previous measurements stored in MEMORY.	
Full Battery	The battery power indicator during measurement.	
Low Battery	The battery is low when it blinks.	Replace all batteries with new ones, when the indicator blinks.
	Unstable blood pressure due to movement during the measurement.	Try the measurement again. Remain very still during the measurement.
Err	The systolic and diastolic values are within 10 mmHg of each other.	
	The pressure value did not increase during inflation.	Fasten the cuff correctly, and try the measurement again.
Err [UF	The cuff is not fastened correctly.	ino modoli omoni again.
Err PUL. DISPLAY ERROR	The pulse is not detected correctly.	
SYS.	Systolic blood pressure in mmHg	
DIA.	Diastolic blood pressure in mmHg	
PUL./min.	Pulse per minute	
CE 0123	EC directive medical device label	
EC REP	EU-representative	
	Manufacturer	
	Class II device	
X	WEEE label	
8	Refer to instruction manual/booklet	

Symbols	Function / Meaning	Recommended Action
SN	sn Serial number	
⊖-€-⊕	Polarity of DC jack	

Operation Mode

1. Normal Measurement With Storing Data (Refer to page 9)

Press the <u>START</u> button. Blood pressure is measured and data is stored within the device. The device can store the last ninety sets of data in memory automatically.

2. Recalling Data (Refer to page 11)

When nothing is displayed, press the <u>MEMORY</u> button to appear the data number. The data number of the most recent measurement and the data are displayed. Stored data are automatically displayed in order from the last data.



3. Clearing Data (Refer to page 11)

Remove batteries to clear all data. Re-install them again.

4. Measurement With The Desired Systolic Pressure

Refer to page 10 for the measurement with the desired systolic pressure.

Using the Monitor

Installing / Changing The Batteries

- 1. Remove the battery cover.
- Remove the used batteries and insert new batteries into the battery compartment as shown, taking care that the polarities (+) and (-) are correct.
- 3. Replace the battery cover. Use only R6P, LR6 or AA batteries.

CAUTION

- Insert the batteries as shown in the battery compartment. If not, the device will not work.
- When (LOW BATTERY mark) blinks on the display, replace all batteries with new ones. Do not mix old and new batteries. It may shorten the battery life, or cause the device to malfunction.
- □ □ (LOW BATTERY mark) does not appear when the batteries are drained.
- Battery life varies with the ambient temperature and may be shorter at low temperatures.
- Use the specified batteries only. The batteries provided with the device are for testing monitor performance and may have a limited life.
- Remove the batteries if the device is not to be used for a long time.
 The batteries may leak and cause a malfunction.
- The stored data are cleared when the batteries are removed.
- When the AC adapter is used for measurement, memories are cleared after pulling out the AC adapter.

Installing The Cuff Holder

This device comes equipped with a removable cuff holder for your convenience. When not in use, simply slip your cuff into the holder for storage.

To install the cuff holder:

- 1. Align the cuff holder with the rear of the device.
- 2. Slide the cuff holder into the rear of the device until it snaps securely into place.

To remove the cuff holder:

- 1. Push the tab on the cuff holder away from the device.
- 2. Slide the cuff holder away from the device as shown.









Selecting The Correct Cuff

Using the correct cuff size is important for an accurate reading. If the cuff is not the proper size, the reading may yield an incorrect blood pressure value.

- The arm size is printed on each cuff.
- If your arm size is over 32 cm, the Large cuff is proper.

Arm Size	Recommended Cuff Size	Catalog Number
22 cm to 43 cm	Large adult cuff	CUF-U-LA
17 cm to 32 cm	Adult cuff	CUF-U-A

Arm size: The circumference at the biceps.

Note: Model UA-782 is NOT designed for using a small cuff.

Symbols printed on the cuff.

Symbols	Function / Meaning	Recommended Action
	Artery position mark	Set the mark on the artery of the upper arm or in line with the ring finger on the inside of the arm.
REF	Catalog number	
LOT	Lot number	

Using the Monitor

Applying The Arm Cuff

- Wrap the cuff around the upper arm, about 1 to 2 cm above the inside of the elbow, as shown.
 Place the cuff directly against the skin, as clothing may cause a faint pulse and result in a measurement error.
- 2. Constriction of the upper arm, caused by rolling up a shirtsleeve, may prevent accurate readings.



How To Take Proper Measurements

For the most accurate blood pressure measurement:

- Sit comfortably on a chair. Rest your arm on the table. Do not cross your legs. Keep your feet on the floor and straighten your back.
- Relax before measurement.
- Place the center of the cuff at the same height as your heart.
- Remain still and keep quiet during measurement.
- Do not measure immdiately after physical exercise or a bath. Rest before taking the measurement.
- Try to measure your blood pressure at the same time every day.

Measurement

During measurement, it is normal for the cuff to feel very tight. (Do not be alarmed)

After Measurement

After measurement, press the <u>START</u> button to turn off the power. Remove the cuff and record your data.

Note: The device has an automatic power shut-off function, which turns the power off approximately one minute after measurement. Allow at least three minutes between measurements on the same person.

Measurements

Model UA-782 is designed to detect the pulse and to inflate the cuff to a systolic pressure level automatically.

If your systolic pressure is expected to exceed 230 mmHg, read

"Measurement With The Desired Systolic Pressure" on the next page.

Normal Measurement

- 1. Place the cuff on the arm (preferably the left arm). Sit quietly during measurement.
- 2. Press the START button.

The average blood pressures and last data number are displayed briefly.

Then the display changes, as indicated in the figure at the right, as the measurement begins. The cuff starts to inflate. It is normal for the cuff to feel very tight.

A pressure bar indicator is displayed, as in the figure at the right, during inflation.

- 3. When inflation is complete, deflation starts automatically and the ♥ (heart mark) blinks, indicating that the measurement is in progress. Once the pulse is detected, the mark blinks with each pulse beat.
 - Note: If an appropriate pressure is not obtained, the device starts to inflate again automatically.
- 4. When the measurement is complete, the systolic and diastolic pressure readings and pulse rate are displayed. The cuff exhausts the remaining air and deflates completely.
- 5. Press the START button again to turn off the power.





Note: If you wish to stop inflation at any time, press the START button again.

Measurements

Measurement With The Desired Systolic Pressure

If your systolic pressure is expected to exceed 230 mmHg, use this procedure.

- 1. Place the cuff on the arm (preferably the left arm).
- 2. Press and hold the <u>START</u> button until a number about 30 to 40 mmHg higher than your expected systolic pressure appears.
- 3. Release the START button to start measurement, when the desired number is reached. Then continue to measure your blood pressure as described on the previous page.



Notes For Proper Measurement

- Sit down in a comfortable position. Place the arm to be used for the measurement on a table or other support so that the center of the cuff will be at the same height as your heart.
- Relax before taking a measurement. If you are excited or depressed by emotional stress, the measurement will reflect this stress as a higher (or lower) than normal blood pressure reading and the pulse reading will usually be faster than normal.
- An individual's blood pressure varies constantly, depending on what you are doing and what you have eaten. What you drink can have a very strong and rapid effect on your blood pressure.
- This device bases its measurements on the heartbeat. If you have a very weak or irregular heartbeat, the device may have difficulty determining your blood pressure.
- Should the device detect a condition that is abnormal, it will stop the measurement and display an error symbol. Refer to page 4 for the description of the symbols.
- This device is intended for use by adults only. Consult with your physician before using this device on a child. A child should not use this device unattended.

About Memory

The device automatically stores up to ninety blood pressure and pulse measurements in memory. Data stored in memory are assigned a data number in the order of the newest to the oldest. The oldest data displays as "n01". The M symbol in the lower left corner of the display indicates that you are viewing previous data stored in memory.

Recalling Data

- 1. When nothing is displayed, press the <u>MEMORY</u> button. The data number of the most recent measurement and the data are displayed.
- 2. If you want to see the previous data, press the <u>MEMORY</u> button until getting the data you want.
- 3. The display will shut off automatically one minute after you press the MEMORY button.

Clearing Data

To clear all data stored in memory:

- Press and hold the <u>MEMORY</u> button until the "M'(memory) mark blinks three times.
- Remove the batteries and press the <u>START</u> or the <u>MEMORY</u> button. Re-install them again.

If there is no stored data in the memory, "--" will appear.





Note: If press the START button when recalling data, the display shuts off.

What Is An Irregular Heartbeat

Model UA-782 provides a blood pressure and pulse rate measurement even when an irregular heartbeat occurs. An irregular heartbeat is defined as a heartbeat that varies by 25% from the average of all heartbeats during the blood pressure measurement. It is important that you be relaxed, remain still and do not talk during measurements.

Note: We recommend contacting your physician if you see this (O) indicator frequently.



The indicator monitors the progress of pressure during measurement.



WHO Classification Indicator

Each six segments of the bar indicator correspond to the WHO blood pressure classification described on the next page.

WHO Classification Indicator

- Severe hypertension
- Moderate hypertension
 - -Mild hypertension
 - -High normal
 - Normal
 - Optimal
- The indicator displays a segment, based on the current data, corresponding to the WHO classification.



What Is Blood Pressure?

About Blood Pressure

Blood pressure is the force exerted by blood against the walls of the arteries. Systolic pressure occurs when the heart contracts. Diastolic pressure occurs when the heart expands. Blood pressure is measured in millimeters of mercury (mmHg). One's natural blood pressure is represented by the fundamental pressure, which is measured first thing in the morning while one is still at rest and before eating.

What Is Hypertension And How Is It Controlled?

Hypertension, an abnormally high arterial blood pressure, if left unattended, can cause many health problems including stroke and heart attack. Hypertension can be controlled by altering lifestyle, avoiding stress, and with medication under a doctor's supervision.

To prevent hypertension or keep it under control:

- Do not smoke
- Reduce salt and fat intake
- Exercise regularly
- Have regular physical checkups
- Maintain proper weight

Why Measure Blood Pressure At Home?

Blood pressure measured at a clinic or doctor's office may cause apprehension and can produce an elevated reading, 25 to 30 mmHg higher than that measured at home. Home measurement reduces the effects of outside influences on blood pressure readings, supplements the doctor's readings and provides a more accurate, complete blood pressure history.

WHO Blood Pressure Classification

Standards to assess high blood pressure, without regard to age, have been established by the World Health Organization (WHO), as shown in the chart.

Blood Pressure Variations

An individual's blood pressure

varies greatly on a daily and seasonal basis. It may vary by 30 to 50 mmHg due to various conditions during the day. In hypertensive individuals' variations are even more pronounced. Normally, the blood pressure rises while at work or play and falls to its lowest levels during sleep. So, do not be overly concerned by the results of one measurement.



Take measurements at the same time every day using the procedure described in this manual to get to know your normal blood pressure. Regular readings give a more comprehensive blood pressure history. Be sure to note date and time when recording your blood pressure. Consult your doctor to interpret your blood pressure data.

Troubleshooting			
Problem	Possible Reason	Recommended Action	
Nothing appears	Batteries are drained.	Replace all batteries with new ones.	
on the display, even when the power is turned on.	Battery terminals are not in the correct position.	Reinstall the batteries with negative and positive terminals matching those indicated on the battery compartment.	
The cuff does not inflate.	Battery voltage is too low. (LOW BATTERY mark) blinks. [If the batteries are drained completely, the mark does not appear.]	Replace all batteries with new ones.	
The device does not measure. Readings are too high or too low.	The cuff is not fastened properly.	Fasten the cuff correctly.	
	You moved your arm or body during the measurement.	Make sure you remain very still and quiet during the measurement.	
	The cuff position is not correct.	Sit comfortably and still. Raise your hand so that the cuff is at the same level as your heart.	
		If you have a very weak or irregular heat beat, the device may have difficulty in determining your blood pressure.	
Other	The value is different from that measured at a clinic or doctor's office.	Refer to "Why Measure Blood Pressure At Home"	
		Remove the batteries. Place them back properly and try the measurement again.	

Note: If the actions described above do not solve the problem, contact the dealer. Do not attempt to open or repair this product, as any attempt to do so will make your warranty invalid.

Maintenance

Do not open the device. It uses delicate electrical components and an intricate air unit that could be damaged. If you cannot fix the problem using the troubleshooting instructions, request service from your dealer or from the A&D service group. The A&D service group will provide technical information, spare parts and units to authorized dealers.

The device was designed and manufactured for a long service life. However it is generally recommended to have the device inspected every 2 years, to ensure proper functioning and accuracy. Please contact either your authorized dealer or A&D for maintenance.

-			
	Techr	nical Data	
Туре	UA-782		
Measurement method	Oscillomet	ric measurement	
Measurement range	Pressure:	20 – 280 mmHg	
	Pulse:	40 – 180 beats / minute	
Measurement accuracy	Pressure:	±3 mmHg	
	Pulse:	±5%	
Power supply		atteries (R6P, LR6 or AA) oter (TB-233) (Not included)	
Number of measurements	Approximately 450 measurements, when AA Alkaline batteries are used, with pressure value of 180 mmHg at room temperature of 23 °C.		
Classification	Internally powered ME equipment (Supplied by batteries) / Class II (Supplied by adapter) Continuous operation mode		
Clinical test	According to ANSI / AAMI SP-10 1987		
EMC	IEC 60601	-1-2: 2007	
Memory	Last 90 me	asurements	
Operating conditions	+10 °C to + 800 to 106	-40 °C / 15 %RH to 85 %RH / 0hPa	
Transport / Storage conditions	s −10 °C to +	-60 °C / 15 %RH to 95 %RH	
Dimensions	Approx. 11	6 [W] x 88.5 [H] x 146.5 [D] mm	
Weight	Approx. 32	0 g, excluding the batteries	
Applied part	Cuff Type	BF 🖈	

Useful life	Device: Cuff:	5 years (when used six times a day) 2 years (when used six times a day)
Accessory AC adapter	The adapte source at h	r is to connect the device to a power ome.
TB-233		tact your local A&D dealer for purchasing. apter is required to be inspected or priodically.
TB-233C		00-240∨ V 500mA ℃ ⊏- □
TB-233BF		$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
A		

Accessories sold separately

Catalog Number	Cuff Size	Arm Size
CUF-U-LA	Large adult cuff	22 cm to 43 cm
CUF-U-A	Adult cuff	17 cm to 32 cm

Arm size: The circumference at the biceps.

AC adapter

Cuff

Catalog Number	Plug (Outlet type)
TB-233C	Туре С
TB-233BF	Type BF

Note: Specifications are subject to change without prior notice.

EMC table information is listed on our website:

http://www.aandd.jp/products/manual/medical/emc_acadapter_en.pdf



🖬 A&D Company, Limited

1-243 Asahi, Kitamoto-shi, Saitama 364-8585 JAPAN Telephone: [81] (48) 593-1111

Fax: [81] (48) 593-1119

EC REP A&D INSTRUMENTS LIMITED

Unit 24/26 Blacklands Way, Abingdon Business Park, Abingdon, Oxfordshire OX14 1DY United Kingdom Telephone: [44] (1235) 550420 Fax: [44] (1235) 550485

A&D ENGINEERING, INC.

1756 Automation Parkway, San Jose, California 95131 U.S.A. Telephone: [1] (408) 263-5333 Fax: [1] (408)263-0119

A&D AUSTRALASIA PTY LTD

32 Dew Street, Thebarton, South Australia 5031 AUSTRALIA Telephone: [61] (8) 8301-8100 Fax: [61] (8) 8352-7409