

The AD-1688 weighing data logger is a handheld device that lets you collect weighing data without connecting the balance or scale to a PC!



Dual Interface

An RS-232C interface to import weighing data from an A&D balance or scale and a USB interface to export the data to a PC (no driver software is required)

Large Memory

Approx. 5,000 weighing data sets (in the A&D standard format) can be stored

Internal Clock

The date and time the data is saved is stored in data

Highly Portable

Small size and IP65 dust and waterproof (with the casing cover)

No Battery Required

Receives power supply directly from a balance, scale or PC

(Actual size)



The AD-1688 is especially useful when a PC or printer cannot be placed near the balance or when you need to collect data from multiple balances at different locations (such as in a factory)





..Clearly a Better Value

AD-1688 Specifications

Applicable devices	Balances and scales with an RS-232C connector manufactured by A&D	
Memory size	Approx. 5,000 data sets in the standard format (15 characters in 1 data set) can be stored	
Clock error	±1 minute / month	
Applicable OS	Windows 2000 / XP / Vista	
Dedicated power supply	Not required. Power is supplied by the weighing instrument or PC.	
Operating environment	environment 5 °C to 40 °C (41 °F to 104 °F), 85 %RH or less (no condensation)	
Dimensions	ons 55 × 103 × 16.5 mm	
Weight	Approx. 60 g	

Standard Accessories

USB extension cable (0.5 m) Three RS-232C cables (1 m) with a D-sub 9-pin connector with a D-sub 25-pin connector with a 7-pin DIN connector

The data is stored in CSV format and can be used easily by software such as Microsoft Excel.

🛍 б	le <u>E</u> dit	View Insert Fg	rmat <u>T</u> ools <u>D</u>	ata <u>W</u> indo	w <u>H</u> elp	_10	7 X
	B9	-	=				
	Α	в	С	D	E	F	-
1	1	6/10/2009	10:41:24	ST	3.076	g	
2	2	6/10/2009	10:41:36	ST	3.082	g	
3	3	6/10/2009	10:42:06	ST	3.102	g	
4	4	6/10/2009	10:42:38	ST	3.058	g	
5	5	6/10/2009	10:42:55	ST	3.091	g	
6	6	6/10/2009	10:43:01	ST	3.089	g	
7							-



Transmits weighing data directly from an A&D balance or scale to a USB port of a PC (no driver software is required)*

Sends weighing data to software applications such as Microsoft Excel, Word, and Notepad

Small size and IP65 dust and waterproof (with the casing cover) *Only unidirectional communication from a balance or scale to a PC is possible.

AD-8527 Specifications

Applicable devices	Balances and scales with an RS-232C connector		
	manufactured by A&D		
Dedicated power supply	Not required. Power is supplied by the weighing		
	instrument or PC.		
Operating environment	5 °C to 40 °C (41 °F to 104 °F), 85% RH or less		
	(no condensation)		
Dimensions	55 × 103 × 16.5 mm		
Weight	Approx. 60 g		
Standard accessories	USB extension cable (0.5 m), Three RS-232C cables (1 m)		





..Clearly a Better Value

A&D Company, Limited

3-23-14 Higashi-Ikebukuro, Toshima-ku, Tokyo 170-0013 JAPAN Telephone:[81](3) 5391-6132 Fax:[81](3) 5391-6148 http://www.aandd.jp

ND Quick USB Adapter

AD-8527

A&D ENGINEERING, INC.

1756 Automation Parkway, San Jose, CA 95131 U.S.A. Telephone:[1](408) 263-5333 Fax:[1](408) 263-0119

A&D Australasia Pty Ltd. 32 Dew Street, Thebarton, South Australia 5031 AUSTRALIA Telephone:[61](8) 8301-8100 Fax:[61](8) 8352-7409

A&D INSTRUMENTS LTD.

Unit 24/26 Blacklands Way Abingdon Business Park, Abingdon, Oxon OX14 1DY UNITED KINGDOM Telephone:[44](1235) 550420 Fax:[44](1235) 550485 <German Sales Office>

Große Straße 13 b 22926 Ahrensburg GERMANY Telephone:[49](0) 4102 459230 Fax:[49](0) 4102 459231

A&D KOREA Limited Manhattan Bldg. 8F, 36-2 Yoido-dong, Youngdeungpo-gu, Seoul, KOREA Telephone:[82](2) 780-4101 Fax:[82](2) 782-4280

A&D RUS CO., LTD.

Vereyskaya str.17, Moscow, 121357 RUSSIA Telephone: [7] (495) 937-33-44 Fax: [7] (495) 937-55-66

A&D Instruments India Private Limited 509 Udyog Vihar Phase V Gurgaon-122 016, Haryana, INDIA Telephone: [91](124) 471-5555 Fax: [91](124) 471-5599